

## NEBRASKA ADMINISTRATIVE CODE

### Title 117 - NEBRASKA DEPARTMENT OF ENVIRONMENTAL QUALITY

#### Chapter 2 - APPLICATION OF STANDARDS

001 These standards apply at all times to all surface waters of the State except where noted below. Impounded waters designated by the Department as wastewater treatment facilities, wastewater retention facilities, or irrigation reuse pits are by definition (Chapter 1) not surface waters, thus standards do not apply to these waters.

002 The water quality criteria which may be necessary to protect downstream beneficial uses are applicable to all surface waters, whether or not those beneficial uses are assigned to a given water body in these Standards.

003 The application of standards for streams is be in accordance with Chapters 3, 4, and 5.

004 The application of standards for lakes and impounded waters is in accordance with Chapters 3, 4, and 6. Lakes and impounded waters not identified in Chapter 6 are protected for the assigned beneficial uses of the stream segments (Chapter 5) on which they are located. Water quality criteria associated with such beneficial uses are applicable to these lakes and impounded waters. Lakes not identified in Chapter 6 that are not located on stream segments are to be protected in accordance with 009 of this chapter.

004.01 In lakes and impoundments, or portions thereof, which exhibit natural thermal stratification, all applicable narrative and numerical criteria, with the exception of the numerical criteria for temperature, apply only to the epilimnion. Numerical temperature criteria apply at all depths (epilimnion, metalimnion, and hypolimnion) of lakes and impoundments exhibiting natural thermal stratification. In lakes and impoundments, or portions thereof, not exhibiting natural thermal stratification, the applicable narrative and numerical criteria apply at all depths.

005 The application of standards for wetlands is in accordance with Chapters 3 and 7.

006 These standards may be applied through Title 119 - Rules and Regulations Pertaining to the Issuance of Permits Under the National Pollutant Discharge Elimination System and Title 120 - Procedures Pursuant to Section 401 of the Federal Clean Water Act, 33 u.s.c. § 1251 et seq., for Certification by the Department of Activities Requiring a Federal License or Permit which May Result in a Discharge.

## Title 117

### Chapter 2

007 Narrative and numerical water quality criteria associated with aesthetics (Chapter 4, 005) and general criteria and acute toxicity criteria for protection of aquatic life (Chapter 4, 003) apply to all surface waters except as stated below in paragraphs 008, 010, 011, 012, and 013.

008 These standards, except water quality criteria associated with aesthetics (Chapter 4, 005), will not apply to effluents and non-contact cooling water discharges, although these standards are used in deriving effluent limitations pursuant to Title 119 - Rules and Regulations Pertaining to the Issuance of Permits Under the National Pollutant Discharge Elimination System.

009 These standards, except narrative and numerical water quality criteria associated with aesthetics (Chapter 4, 005) and general criteria and acute toxicity criteria for protection of aquatic life (Chapter 4, 003), will not apply to:

009.01 Streams assigned a Coldwater Class A, Coldwater Class B, or Warmwater Class A Aquatic Life use during periods when the flow is less than 0.1 cfs or the 7-day 10-year low flow, unless an assigned beneficial use still exists under these conditions. Thirty-day average ammonia criteria will not apply to these streams during periods when the flow is less than 0.1 cfs or the 30-day 5-year low flow unless an assigned beneficial use still exists under these conditions.

009.02 Streams assigned the Warmwater Class B Aquatic Life use during periods when the flow is less than 1.0 cfs, unless an assigned beneficial use still exists under this condition.

009.03 Undesignated surface waters except as necessary to protect assigned downstream beneficial uses. Acute criteria which are applicable to these surface waters include those applicable for the Warmwater Class B Aquatic Life use.

009.04 Streams during periods when the instantaneous flow is totally composed of effluent or non-contact cooling water discharges, excluding minor amounts of bank seepage, unless an assigned beneficial use still exists under these conditions.

010 These standards, except water quality criteria associated with aesthetics (Chapter 4, 005) and recreation (Chapter 4, 002) will not apply within mixing zones unless specified below.

Mixing zones for the initial assimilation of effluents or wastewaters may be necessary where discharges that have received the applicable level of treatment or control still do not adequately protect the water quality of a receiving stream. Mixing zones are to be limited to as small an

area and volume of a receiving stream as is practical to prevent interference with or impairment of any beneficial uses. The requirements of mixing zones for heat are to be defined on a site-specific basis, in a manner consistent with Section 316 of the Clean Water Act.

010.01 The Department determines the applicability of a mixing zone, and if applicable, the allowable size, location, water quality, and outfall design. The following requirements will be used in defining all mixing zones. These requirements are not intended to define each individual mixing zone, but represent maximum limits which will satisfy most biological, chemical, physical, and radiological considerations. A smaller mixing zone may be required or no zone at all allowed, as necessary, in order to meet these requirements.

010.02 The appropriateness, if any, of establishing a mixing zone for a pollutant which may be bioaccumulative, persistent, carcinogenic, mutagenic, or teratogenic will be carefully evaluated by the Department. In such cases, effects such as potential ground water contamination, known or predicted safe exposure levels for human health, bioaccumulation in aquatic life, fish attraction, sediment deposition, and protection of downstream beneficial uses will be considered.

010.03 Mixing zones established for dissolved oxygen are to take into account the delayed effects caused by oxidation of organic matter and ammonia inside and outside the mixing zone. One-day minimum dissolved oxygen criteria apply at the boundary of and beyond acute mixing zones, but not within acute mixing zones. All applicable dissolved oxygen criteria, including the one-day minimum criteria, are to be met at and beyond the mixing zone boundaries.

010.04 Mixing zones established for discharges impacting agricultural water supply criteria are to be based on the restrictions established for chronic mixing zones (010.06).

010.05 All mixing zone specifications are to be based on critical conditions of minimum dilution. Flow variable calculations that use real-time flows for a point source discharge and receiving stream may be allowed to determine critical conditions of minimum dilution. If flow variable critical conditions are not defined, critical conditions are to be determined as follows. The average dry weather or seasonal flow for a point source discharge will be used with the 7-day 10-year low flow of the receiving stream for application of all criteria with the exception of thirty-day average ammonia criteria and acute criteria for aquatic life. The 30-day 5-year low flow of the receiving stream will be used for application of thirty-day average ammonia criteria. The 1-day 10-year low flow of the receiving stream will be used for application of acute criteria.

010.06 Chronic Mixing Zones.

Chronic toxicity to aquatic life will not be allowed at any time outside of a chronic mixing zone.

010.06A The length of a chronic mixing zone is not to exceed the following distances based on designated aquatic life use classes.

010.06A1 Chronic mixing zones in Coldwater Class A, Coldwater Class B, and Warmwater Class B streams are to be designed to not exceed 2,500 feet in length.

010.06A2 Chronic mixing zones in Warmwater Class A streams are to be designed to not exceed 5,000 feet in length.

010.06B Chronic mixing zones are to be located in a receiving stream in such a manner that the maintenance of aquatic life and other beneficial uses will not be adversely affected.

010.06B1 A chronic mixing zone is not to overlap with any other mixing zone unless it is demonstrated to the satisfaction of the Department (e.g. aquatic field studies, bioassays in the site water using resident or acceptable nonresident aquatic species) that the overlapping of the mixing zones will not result in any adverse effects to aquatic life or other beneficial uses.

010.06B2 Chronic mixing zones are not to at any time:

010.06B2a Extend across public drinking water supply intakes.

010.06B2b Extend across heavily-used or state designated recreation bathing areas.

010.06B2c Extend into publicly owned lakes and reservoirs listed in Chapter 6.

010.06B2d Significantly impact federally and/or state designated threatened or endangered aquatic species.

010.06C Water quality of chronic mixing zones.

The Department may suspend the applicability of all or part of the water quality criteria within a chronic mixing zone, except those criteria relating to aesthetics (Chapter 4, 005) and acute toxicity to aquatic life (Chapter 4, 003.01C). In streams designated a recreational use, criteria relating to recreation (Chapter 4, 002) also apply within a chronic mixing zone. Waters at and beyond chronic mixing zone boundaries are to meet all chronic water quality criteria associated with the receiving stream any time the receiving streamflow is equal to or greater than 0.1 cfs for streams assigned a Coldwater Class A, Coldwater Class B, or Warmwater Class A Aquatic Life use; 1.0 cfs for streams assigned the Warmwater Class B Aquatic Life use; or its 7-day 10-year low flow (30-day 5 year low flow in the case of thirty-day average ammonia criteria), whichever is greater. To prevent chronic toxicity in a stream, the following conditions are to be met.

010.06C1 The pollutant levels or concentrations of wastewaters which contain unknown or complex mixtures of potentially additive or synergistic toxic pollutants are not to exceed 1.0 chronic toxic units (TU<sub>c</sub>) based on chronic bioassays representing the effluent dilution received at the chronic mixing zone boundary.

010.06C2 Where more than one wastewater discharge is located in a specific area and the potential exists for additive or synergistic effects, the pollutant levels or concentrations in water from a receiving stream outside any mixing zone are not to exceed 1.0 TU<sub>c</sub> based on chronic bioassays.

010.06C3 Where a mixing zone is not allowed by the Department, the pollutant levels or concentrations of the wastewater in the outfall structure itself are not to exceed the No Observed Effect Level (NOEL) based on chronic bioassays of the undiluted effluent. NOEL is the threshold concentration of a substance which causes no observed adverse effects to bioassay test organisms under test conditions specified or approved by the Department.

010.07 Acute Mixing Zones.

Acute toxicity to aquatic life will not be allowed at any time outside of an acute mixing zone.

010.07A Acute mixing zones are to allow at all times for a continuous zone of passage in the receiving stream for the movement or drift of aquatic biota. To provide for a zone of passage, the width of an acute mixing zone at any transect of the receiving stream is not to exceed more than 1/2 of the stream width. Where more than one wastewater discharge is located in a specific area, acute mixing zones are to be located in such a manner as to provide for a continuous zone of passage of at least 1/2 the stream width.

010.07B The length of an acute mixing zone is not to exceed the following distances based on designated aquatic life use classes.

010.07B1 Acute mixing zones in Coldwater Class A, Coldwater Class B, and Warmwater Class B streams are to be designed to not exceed 125 feet in length or 5 percent of the length of the chronic mixing zone whichever is more restrictive.

010.07B2 Acute mixing zones in Warmwater Class A streams are to be designed to not exceed 250 feet in length or 5 percent of the length of the chronic mixing zone whichever is more restrictive.

010.07C Acute mixing zones are to be located in a receiving stream in such a manner that the maintenance of aquatic life and other beneficial uses will not be adversely affected. Acute mixing zones are not to at any time:

010.07C1 Extend across public drinking water supply intakes.

010.07C2 Extend across heavily-used or state designated recreation bathing areas.

010.07C3 Extend into publicly owned lakes and reservoirs listed in Chapter 6.

010.07C4 Significantly impact federally and/or state designated threatened or endangered aquatic species.

010.07C5 Extend across the mouth of a classified tributary stream segment.

010.07D Water quality of acute mixing zones.

The Department may suspend the applicability of all or part of the water quality criteria within an acute mixing zone, except those criteria relating to aesthetics (Chapter 4, 005). In streams designated a recreational use, criteria relating to recreation (Chapter 4, 002) also apply within the acute mixing zone. Waters at and beyond acute mixing zone boundaries are to meet all acute water quality criteria associated with the receiving stream any time the receiving streamflow is equal to or greater than 0.1 cfs or its 1-day 10-year low flow.

010.07D1 The pollutant levels or concentrations of wastewaters which contain unknown or complex mixtures of potentially additive or synergistic toxic pollutants are not to exceed 0.3 acute toxic units (TU<sub>a</sub>) based on acute bioassays representing the effluent dilution received at the acute mixing zone boundary.

010.07D2 Where more than one wastewater discharge is located in a specific area and the potential exists for additive or synergistic effects, the pollutant levels or concentrations in water from a receiving stream outside any acute mixing zone are not to exceed 0.3 TU<sub>a</sub> based on acute bioassays.

010.07D3 Where a mixing zone is not allowed by the Department, the pollutant levels or concentration of the wastewater in the outfall structure itself are not to exceed 0.3 TU<sub>a</sub> based on acute bioassays of the undiluted effluent.

010.08 Mixing Zones for Public Drinking Water Supply Criteria.

In waters designated as Water Supplies for Public Drinking Water, the criteria for protection of public drinking water supplies are not to be exceeded at any time outside of a mixing zone for public drinking water supply criteria.

010.08A Mixing zones for public drinking water supply criteria are to be designed to not extend to within a 2 mile zone of influence from any public drinking water supply intake.

010.08B Mixing zones for public drinking water supply criteria are to be located in a receiving stream in such a manner that other beneficial uses will not be adversely affected.

010.08C Water quality of mixing zones for public drinking water supply criteria.

The Department may suspend the applicability of all or part of the water quality criteria for the protection of public drinking water supplies within a mixing zone for public drinking water supply criteria. Waters at and beyond boundaries of mixing zones for public drinking water supply criteria are to meet all public drinking water supply criteria any time the receiving stream is flowing equal to or greater than its 7-day 10-year low flow.

010.09 Outfall Design.

Prior to designating a mixing zone, the Department will first approve pursuant to Title 123 - Rules and Regulations for Design, Operation, and Maintenance of Wastewater Treatment Works that the best practical engineering design for the outfall structure and its location and placement in the receiving stream have been applied, as necessary, to meet all mixing zone requirements for size, location, and water quality.

010.09A The following are acceptable circumstances for modifying the existing design, location, or placement of an outfall structure in a stream:

010.09A1 Where high-rate diffusers or similar devices are required to: (1) minimize or prevent exposure of aquatic biota to acutely toxic conditions within an acute mixing zone, (2) minimize or prevent exposure of aquatic biota to possible irreversible chronic effects within a mixing zone where wastewaters tend to attract aquatic organisms, or (3) otherwise expedite mixing and dispersion of wastewaters in order to meet mixing zone requirements for size, location, and water quality.

010.09A2 Where changes are required in the location of an outfall structure (e.g., upstream, downstream, or to the opposite stream bank) or its placement (e.g., water depth, direction in relation to the stream current)



Title 117

Chapter 2

in order to meet mixing zone requirements for size, location, and water quality.

010.09B Water turbulence created by high-rate diffusers or similar devices is not to be of such a magnitude that the movement or drift of aquatic biota within a zone of passage is interfered with or prevented.

011 Water quality criteria in Chapters 4 and 7 related to aquatic herbicides or algicides and their effects will not apply to waters within canals, except those canals designated as segments in Chapter 5, during periods when these chemicals are applied by an irrigation district for the control of aquatic plants.

011.01 All standards apply at all times to waters within canals designated as segments in Chapter 5.

011.02 Discharges from canal to other surface waters of the State are not to, at any time, contain herbicides or algicides in amounts which are toxic to aquatic life.

012 Water quality criteria in Chapters 4 and 7 related to aquatic biocides (e.g., ichthyocides, algicides, herbicides) and their effects will not apply to surface waters during periods when aquatic biocides are applied by an entity responsible for the management of a surface water body under the following conditions:

012.01 Aquatic biocides are to be applied only for the purposes of attaining, maintaining, or enhancing beneficial uses identified in Chapters 4, 5, 6 and 7.

012.02 Application of aquatic biocides are not to cause adverse impacts to any assigned beneficial uses of surface waters beyond the targeted surface water body.

012.03 Application of aquatic biocides are to be in accordance with the label restrictions and all applicable federal, state, and local laws or regulations.

012.04 Entities responsible for the management of surface water bodies may include the Nebraska Game and Parks Commission, Natural Resources Districts, U.S. Fish and Wildlife Service, U.S. Forest Service, National Parks Service, U.S. Army Corps of Engineers, city governments, or any other entity responsible for managing the surface water body's assigned beneficial uses.

Title 117

Chapter 2

013 These standards will not apply to:

013.01 Waters below existing hydroelectric plants during periods of approved sluicing activities, provided the hydroelectric plant was operational prior to May 10, 1982. The Department will determine when sluicing activities will be allowed.

013.01A Sluicing activities will be conducted in such a manner as to minimize any harmful effects on assigned beneficial uses.

013.01B Sluicing is not to occur immediately before or during critical reproductive periods of identified key species.

013.01C In the event that the sluicing activity has been determined to have a deleterious impact on the aquatic biota of the State waters, the operator is to pay to the Game and Parks Commission annually the lesser of A., \$5000.00, or B., 20% of the annual damages, which is the fair market mitigation to the fisheries resulting from the sluicing activity.

013.02 Waters within canals designated as segments in Chapter 5 during periods of dewatering which are required for or may result from repair, maintenance, inspection, non-diversion periods, force majeure or public safety.

014 Because the frequency and extent of monitoring programs can only approximate whether surface waters meet or exceed water quality criteria that are based on averages over a specified time period in Chapters 4 and 7, assessment of compliance with these criteria may utilize scientifically accepted statistical procedures.

015 Variances.

015.01 Upon written application by any person and meeting the requirements of this section, the director may grant a variance for an interim beneficial use and interim criterion when it is determined that the attainment of a current beneficial use and criterion is not feasible because one of the following conditions is met:

015.01A One of the factors listed in 40 C.F.R 131.10(g) dated July 1, 2018, which is adopted and incorporated by reference, exists.

015.01B Actions necessary to facilitate lake, wetland, or stream restorations through dam removal or other significant reconfiguration activities preclude

attainment of the designated use and criterion while the actions are being implemented.

015.02 Prior to the granting of any variance as allowed by 015.01, persons or categories of facilities eligible for an interim beneficial use and interim criterion will be proposed for adoption by the Nebraska Environmental Quality Council, after a public hearing consistent with 40 C.F.R. 131.20(b) dated July 1, 2018, which is adopted and incorporated by reference. Categories of eligible facilities will be identified and proposed in conjunction with the next systematic review or subsequent triennial review.

015.03 Adoption and implementation of each variance will be in accordance with 40 C.F.R 131.14 dated July 1, 2018, which is adopted and incorporated by reference, except that 131.14(a)(2), 131.14(b)(1)(ii), and 131.14(b)(2)(i)(A) are to be replaced by paragraphs 015.04 through 015.06 of this regulation, respectively.

015.04 Each variance will have a designated term limit and reflect the highest attainable condition during the specified term. A variance may be applied to individual or multiple dischargers or surface water bodies.

015.05 Each variance will have requirements and a time limitation demonstrating the intent that progress be made toward the attainment of the underlying designated use and criterion.

015.05A Each Nebraska surface water quality standard not specifically addressed in a variance will remain applicable.

015.05B Each person requesting a variance is to provide evidence that a designated use and criterion, or a designated use or criterion addressed by the variance cannot be achieved solely by the implementation of technology-based effluent limits.

015.05C Each requirement of the variance is to represent the highest attainable condition of the surface water segment applicable throughout the term of the variance. A specified requirement will not result in lowering the currently attained ambient water quality, unless a variance is necessary for physical reconfiguration activities intended for surface water segment restoration. The highest attainable condition of each affected surface water segment as a quantifiable expression is to be specified as one of the following:

Title 117

Chapter 2

015.05C1 The highest attainable interim criterion;

015.05C2 The interim effluent condition that reflects the greatest pollutant reduction achievable; or

015.05C3 The interim criterion or effluent condition that reflects the greatest pollutant reduction achievable with the pollutant control technologies installed at the time the variance is adopted.

015.05D If the quantifiable expression identified in paragraph 015.05C3 is selected, a pollutant minimization plan consistent with 40 C.F.R 131.3(p) dated July 1, 2018, which is adopted and incorporated by reference, is to be adopted and implemented if no additional feasible pollutant control technology is identified.

015.06 Each variance request will include supporting documentation that demonstrates all of the following:

015.06A Attaining the designated use and criterion is not feasible throughout the term of the variance because of one of the factors cited in paragraphs 015.01A and 015.01B;

015.06B The term of the variance is only as long as necessary to achieve the highest attainable condition; and

015.06C The highest attainable condition of the affected surface water segment is as defined in paragraph 015.05C.

015.07 A discharger that adversely impacts water quality will not be granted a variance from requirements of Title 117, Chapter 3.

015.08 Specific eligibility requirements may be included in a multiple-discharger variance as an alternative to identifying the specific dischargers at the time of adoption of the variance. Each discharger is to meet the eligibility requirements in the applicable section of the “Nebraska Surface Water Quality Standards Variance Register”, which will be made available to the public by the Department on its web site.

Enabling Legislation: Neb. Rev. Stat. §81-1505(1)(2)

Legal Citation: Title 117, Ch. 2, Nebraska Department of Environmental Quality